



FEATURES

All air tanks are manufactured to ASNZS1200 Standards

PRODUCT TIPS

Always fit a Pressure Relief Valve approx. 17% above the pressure switches rating as the Pressure relief valve can start to relieve air pressure below its rating.

BENEFITS

- 20 foot power lead and inline fuse for compressor protection
- Automatic Thermal Cut-off switch – Protects compressor from damage caused by excessive heat during operation
- Tyre Seat Re-beading

Kingsley Enterprises Pty Ltd
Ph: 1800 654 767 | Fax: 1800 655 196
International: +61 2 8700 0400
sales@kingsleyenterprises.com.au
www.bushranger.com.au

Air Tank

Created: 18th April 2011
Revised: 19th November 2012

VEHICLE APPLICATIONS

Specially designed for multiple applications, including:

- Diff-Lockers
- Air-bag Suspension
- Pneumatic Tools (including trade applications)
- Fast Inflation of Tyres and Tyre Re-beading

SPECIFICATIONS:

Part Number: 1048

Description: 1 Gallon – 3 port Tank – ¼ “ NPT

Warranty: 1 Year Warranty

Diameter: 155mm

Bracket Height: 40mm

Overall Dimensions: 210mm (H) x 155mm (W)
x 300mm (L)

Part Number: ABR144

Description: 5 Gallon – 7 port Tank – ¼ “ NPT

Warranty: 1 Year Warranty

Diameter: 205mm

Bracket Height: 45mm

Overall Dimensions: 265mm (H) x 205mm (W)
x 570mm (L)

ALWAYS MOUNT A PRESSURE RELIEF VALVE TO ENSURE YEARS OF SAFE USAGE FROM YOUR TANK. REMEMBER TO MOUNT THE DRAIN PLUG AT THE LOWEST POINT ON THE TANK TO REMOVE ANY COLLECTED WATER