DTX4300VP ANU220 6.5dBi ANTENNA

10

(1-1)



IP54 DUST AND SPLASH RESISTANT



5 YE

YEAR WARRANTY^{*}



DTX4300PK MICROSIZE 5 WATT UHF CB RADIO + ANU220 ANTENNA



The Oricom DTX4300 Micro Size 5 Watt UHF CB radio is a well-crafted unit, packing a real punch for its ultracompact size, and is one of the smallest fixed mount UHF CB radios on the Australian market. Pack includes ANU220 6.5dBi Antenna.

KEY FEATURES

- Ultra compact micro size
- 96 colour LCD backlit display
- Flip LCD function
- Over voltage alert function
- Heavy duty microphone
- 3 memory groups
- Smart fast scanning (priority/ group memory/ group tone scan)
- Back light brightness (4 pre-set levels plus auto)
- Rotary volume/channel and squelch control
- Duplex
- 38 CTCSS & DCS codes
- Diecast metal chassis
- Auto power off (off/1h/2h/4h)
- 3.5mm external jack (for optional external speaker)
- Designed and engineered in Korea

DTX4300 Technical Specification

| GENERAL | |
|-----------------------------|---------------------------------------|
| Compliance | AS/NZS 4365:2011 |
| Frequency Range TX/RX | 476.425 - 477.4125 MHz |
| Number of TX/RX Channels | 80 UHF CB Channels (75 voice) |
| Channel Spacing TX/RX | 12.5KHz |
| Operating modes | Simplex, Repeater TX offset (+750KHz) |
| Scanning Speed | 50 msec per channel |
| Antenna Impedance | 50 Ohms |
| Operating Volts nominal | 13.8VDC |
| Operating Volts Range | 10 to 16 VDC |
| Over Voltage Protection | Diode and Voltage regulator system |
| Over Current Protection | 2 AMP fuse |
| Reverse Polarity Protection | Shunt diode |
| Frequency stability | +/- 5 ppm |
| | |

TRANSMITTER

| RF Output Power | 5 watts max |
|-------------------------------|---|
| Modulation | F3E(FM) |
| Maximum deviation | 2.5KHz |
| Spurious Emissions | <-30dBm |
| TX Audio pre-emphasis | +6dB/Octave from 300Hz to 3KHz |
| Current consumption during TX | 1.7 AMP with 50 ohm antenna termination |

RECEIVER

| Circuit Type | Dual conversion superheterodyne |
|-----------------------------|------------------------------------|
| Intermediate Frequencies | 1st IF = 21.4MHz , 2nd IF = 450kHz |
| Maximum useable sensitivity | -123dBm for 12dB SINAD |
| Audio output power | 2 Watts at 8 ohm load |
| RX Audio de-emphasis | -6dB/octave 300Hz to 3kHz |

MECHANICAL

Dimensions (H) X (W) X (D)

22.5 (d) x 100 (w) x 76 (h) mm

Weight





210g transceiver only

IP54 DUST AND

SPLASH RESISTANT

5 YEAR WARRANTY*

*5 Year Warranty applies to DTX4300 UHF CB Radio only.



oricom.com.au

Oricom® is the registered trademark of Oricom International Pty Ltd