


CONTROLLED RHINO-RACK

*Note: RLT600 Parts as separate.

- Mark hole points through each bracket.
- Centre punch marked hole positions.
- Drill Ø5mm holes.
- Vacuum swarf and clean after drilling.
- Apply Cold Galvanising paint to holes.
- Apply Butyl patches concentric with each drilled hole.
- Locate the rivets through each bracket into drilled holes. Set all rivets.
- Fasten RLT600 base as per instructions



Item	Component Name	Qty	Part No.
1	Stavex Rivet BS 11 4.8mm	4	H060
2	Butyl Patch	4	CA1556
3	M8 x 12mm Button Head Screw	2	B081
4	M8 Shake Proof Washer	2	W033
5	M8 x 17mm Flat Washer	2	W020
6	RLT600 High Skirt	2	M829
7	Quick Mount Bracket LH Front	1	CA1635
8	Quick Mount Bracket RH Front	1	CA1634
9	Instructions	1	R1006

on the Rhino-Rack web site for comprehensive instructions on fitting racks to your vehicle.

Please refer

to 'Fit My Car'

Issue: 02

Document No: R1006

Prepared by: Kayle Everett

CONTROLL

RHINO-RACK

*Note: RLT600 Parts as separate.

- Mark hole points through each bracket.
- Centre punch marked hole positions.
- Drill Ø5mm holes.
- Vacuum swarf and clean after drilling.
- Apply Cold Galvanising paint to holes.
- Apply Butyl patches concentric with each drilled hole.
- Locate the rivets through each bracket into drilled holes. Set all rivets.
- Fasten RLT600 base as per instructions.

3. 11. 4.⊕ €5.	2 .
	≥ 6.
7.	8.
· · •	

Item	Component Name	Qty	Part No.
1	Stavex Rivet BS 11 4.8mm	4	H060
2	Butyl Patch	4	CA1556
3	M8 x 12mm Button Head Screw	2	B081
4	M8 Shake Proof Washer	2	W033
5	M8 x 17mm Flat Washer	2	W020
6	RLT600 High Skirt	2	M829
7	Quick Mount Bracket LH Front	1	CA1635
8	Quick Mount Bracket RH Front	1	CA1634
9	Instructions	1	R1006

to 'Fit My Car' on the Rhino-Rack web site for comprehensive instructions on fitting racks to your vehicle.

Please refer

Issue: 02


Document No: R1006

Prepared by: Kayle Everett

RHINO-RACK

QMFK09

- *Note: RLT600 Parts as separate.
- Mark hole points through each bracket. - Centre punch marked hole positions.
- Drill Ø5mm holes.
- Vacuum swarf and clean after drilling.
- Apply Cold Galvanising paint to holes. Apply Butyl patches concentric with
- each drilled hole. Locate the rivets through each bracket
- into drilled holes. Set all rivets. Fasten RLT600 base as per instructions



Item	Component Name	Qty	Part No.
1	Stavex Rivet BS 11 4.8mm	4	H060
2	Butyl Patch	4	CA1556
3	M8 x 12mm Button Head Screw	2	B081
4	M8 Shake Proof Washer	2	W033
5	M8 x 17mm Flat Washer	2	W020
6	RLT600 High Skirt	2	M829
7	Quick Mount Bracket LH Front	1	CA1635
8	Quick Mount Bracket RH Front	1	CA1634
9	Instructions	1	R1006

Please refer to 'Fit My Car' on the Rhino-Rack web site for comprehensive instructions on fitting racks to your vehicle.

Issue: 02 Document No: R1006 Prepared by: Kayle Everett

RHINO-RACK

QMFK09

*Note: RLT600 Parts as separate.

- Mark hole points through each bracket.
- Centre punch marked hole positions.
- Drill Ø5mm holes.
- Vacuum swarf and clean after drilling.
- Apply Cold Galvanising paint to holes.
- Apply Butyl patches concentric with each drilled hole.
- Locate the rivets through each bracket into drilled holes. Set all rivets.



Please refer to 'Fit My Car' on the Rhino-Rack web site for comprehensive instructions on fitting racks to vour vehicle.

CONTROLLED

Document No: R1006 Issue: 02

Instructions

Prepared by: Kayle Everett

CONTROL

R1006

RHINO-RACK

QMFK09

9

*Note: RLT600 Parts as separate.

- Mark hole points through each bracket.
- Centre punch marked hole positions.
- Drill Ø5mm holes.
- Vacuum swarf and clean after drilling.
- Apply Cold Galvanising paint to holes.
- Apply Butyl patches concentric with each drilled hole.
- Locate the rivets through each bracket into drilled holes. Set all rivets.

гази	en Kurooo base as per instruction	5.	
tem	Component Name	Qtv	

Item	Component Name	Qty	Part No.
1	Stavex Rivet BS 11 4.8mm	4	H060
2	Butyl Patch	4	CA1556
3	M8 x 12mm Button Head Screw	2	B081
4	M8 Shake Proof Washer	2	W033
5	M8 x 17mm Flat Washer	2	W020
6	RLT600 High Skirt	2	M829
7	Quick Mount Bracket LH Front	1	CA1635
8	Quick Mount Bracket RH Front	1	CA1634
9	Instructions	1	R1006
Issue: 02 Document No: R1006		;	Prepare

on the Rhino-Rack web site for comprehensive instructions on fitting racks to your vehicle.

Please refer

to 'Fit My Car'

Prepared by: Kayle Everett

RHINO-RACK

QMFK09

*Note: RLT600 Parts as separate.

- Mark hole points through each bracket.
- Centre punch marked hole positions.
- Drill Ø5mm holes.
- Vacuum swarf and clean after drilling.
- Apply Cold Galvanising paint to holes.
- Apply Butyl patches concentric with each drilled hole.
- Locate the rivets through each bracket into drilled holes. Set all rivets.
- Fasten RLT600 base as per instructions



Please refer to 'Fit My Car' on the Rhino-Rack web site for comprehensive instructions on fitting racks to your vehicle.

Issue: 02 Document No: R1006 Prepared by: Kayle Everett

